


iSignager Players Selection Guide



iSignager-300 Series

Model		iSIGNAGER-300-R10	iSIGNAGER-300WL-R10
Video Input	Composite		N/A
	DVI		N/A
Video Output	Analog VGA	D-sub 1-pin, up to 720 x 480 with Scaler upto 1366 x 768	
	S-Video		N/A
	Composite		N/A
			N/A
Audio Input			N/A
Audio Output		3.5mm Jack	
LAN		1 x 10/100mBase-T	
Wireless		N/A	802.11b/g wireless
USB		1 x USB	
RS-232		1 x RS-232	
HDD Drive Bay		N/A	
SSD Drive Bay		1 x SD Memory Card Spec. 2.0 Slot	
Construction Material		ABS+ PC Plastic	
Dimensions		216 x 122.1 x 36.7 mm	
Mounting		VESA 75	
Power Input		12VDC power adapter, 90VAC~240VAC input @5~60Hz, 36W	
Power Consumption		6W	
Operation Temperature		0°C~50°C	
Net Weight		0.7 KG	
EMC/Safety		CE, FCC, UL	

1
Automation
Panel
Solutions

2
All-in-One
Touch POS

3
Digital
Signage

4
Video Wall
Controller

5
RISC-
based
Solutions

6
PACSmate
Medical

7
Optional
Peripherals

3-2



iSignager-500A Series

Model		iSignager-500A-R10	iSignager-500AWL-R10
Video Input	Composite		RCA x 1
	DVI	VESA DVI-I connector x 1, up to 1920 x 1080 p @ 60Hz with the H/W scaler	
Video Output	Analog VGA	D-sub 1-pin, up to 1920 x 1200	
	S-Video	Mini-DIN 4 pin connector x 1	
	Composite	RCA x 1	
		Unbalanced stereo RCA jack x 2	
Audio Input		Unbalanced stereo RCA jack x 2	
Audio Output		Unbalanced stereo RCA jack x 2, S/PDIF x1	
LAN		RJ-45 x 1	
Wireless		N/A	802.11b/g wireless
USB		USB A-type Connector x 2	
RS-232		2 x RS-232	
HDD Drive Bay		2.5" IDE HDD bay	
SSD Drive Bay		1 x CF Type II slot	
Construction Material		ABS+ PC Plastic (front panel) Heavy duty steel	
Dimensions		187.2 x 133.7 x 46 mm	
Mounting		VESA 75	
Power Input		12VDC power adapter, 90VAC~240VAC input @5~60Hz, 45W	
Power Consumption		8W	
Operation Temperature		0°C~50°C	
Net Weight		1.2 KGS	
EMC/Safety		CE, FCC, UL	



iSignager-510H Series

Model		iSignager-510H-R10	iSignager-510HWL-R10
Video Input	Composite		RCA x 1
	HDMI	VESA HDMI connector x 1, up to 1920 x 1080 p @ 60Hz with the H/W scaler	
Video Output	Analog VGA	D-sub 1-pin, up to 1920 x 1200	
	S-Video	Mini-DIN 4 pin connector x 1	
	Composite	RCA x 1	
		Unbalanced stereo RCA jack x 2	
Audio Input		Unbalanced stereo RCA jack x 2	
Audio Output		Unbalanced stereo RCA jack x 2, S/PDIF x1	
LAN		RJ-45 x 1	
Wireless		N/A	802.11b/g wireless
USB		USB A-type Connector x 2	
RS-232		2 x RS-232	
HDD Drive Bay		2.5" IDE HDD bay	
SSD Drive Bay		1 x CF Type II slot	
Construction Material		ABS+ PC Plastic (front panel) Heavy duty steel	
Dimensions		187.2 x 133.7 x 46 mm	
Mounting		VESA 75	
Power Input		12VDC power adapter, 90VAC~240VAC input @5~60Hz, 45W	
Power Consumption		8W	
Operation Temperature		0°C~50°C	
Net Weight		1.2 KGS	
EMC/Safety		CE, FCC, UL	