

iSignager Selection Guide

iSignager-Frame Series



Model		iSignager-Frame-W07	iSignager-Frame-08	iSignager-Frame-W10	iSignager-Frame-W15
LCD	LCD Size	7" (Wide Screen)	8"	10.4"(Wide Screen)	15.6"(Wide Screen)
	Max Resolution	800 x 480	800 x 600	1024 x 600	1366 x 768
	Brightness (cd/m ²)	300	300	400	250
	Contrast Ratio	500:1	400:1	400:1	500:1
	LCD Color	262 K	262 K	262 K	16.7 M
	Pixel Pitch (mm)	0.1905(H) x 0.1905(V)	0.2025(H) x 0.2025(V)	0.2175(H) x 0.2175(V)	0.252(H) x 0.252(V)
	Viewing Angle (H-V)	140 / 120	130 / 120	140 / 110	90 / 65
	Backlight MTBF	20000	30000	40000	50000
	Second Display	1 x VGA	1 x VGA	1 x VGA	1 x VGA
	USB	1 x USB 2.0			
Ethernet	1 x 10/100mBase-T				
Wireless	Optional 802.11 b/g wireless (Internal Antenna)				
Serial Port	1 x RS-232				
Audio out	built-in 1.5W+ 1.5W AMP speaker 1 x 3.5mm audio phone jack			built-in 2W+ 2W AMP speaker 1 x 3.5mm audio phone jack	
Remote Control	Panel on/off, Volume Control, Brightness				
Storage	HDD Drive Bay	N/A	N/A	N/A	1 x 2.5" IDE HDD Slot
	SSD Drive Bay	1 x SD Memory Card Spec. 2.0 Slot			
Power	Input Voltage	12VDC in			
	Power adapter	40W ACDC Power Adapter, 90VAC~240VAC @50~60Hz input			
	Consumption	17W	17W	18W	20W
Mounting	VESA Mount 75			VESA Mount 100	
LED Function	1 x Power ON/OFF LED on the front panel				
Operation Temperature	0°C~50°C				
Dimension (WxLxD) (mm)	226 x 140 x 41	234 x 184 x 42	280 x 251 x 49	400 x 273 x 62.9	
Net Weight (Kgs)	0.6	0.8	1.4	3.3	
Front Panel Protection	IP64				
EMC/Safety	CE, FCC, UL				

1

Automation Panel Solutions

2

All-in-One Touch POS

3

Digital Signage

4

Video Wall Controller

5

RISC-based Solutions

6

PACSmate Medical

7

Optional Peripherals