



Introduction

The iSignager-500 Digital Signage Player is a multimedia device that allows you to design and show dynamic audio and video content to your target audience on all types of displays. You can update your advertisement anytime, anywhere over a LAN or Wireless Network. It is equipped to organize high-quality video, audio, graphics, flash, and scrollable banners on a wide range of displays using DVI, AV-video, S-video, VGA, or component video. The graphic interface and design software allows you to quickly create displays with multiple display zones each with its own schedule, customize playlists, and multiple schedules for the player.

Features

- Compact Fanless Player perfect for harsh or outdoor applications
- Auto play after power on
- Real time Video/Audio Inputs
- Built-in WIFI (iSignager-500AWL)
- Supports Multiple formats
- Fully programmable display zones that can show different contents simultaneously, including graphics, real time or recorded video, scrolling messages, audio, and current time.
- Flexible zone/display scheduling
- Easy to use graphical drag and drop design software

Main Specifications

Video Input	NTSC Composite Video	(1) RCA Jack
Video Outputs	DVI	(1) VESA DVI-I (DVI+ VGA) Connector, up to 1920 x1200 @ 60Hz with H/W scaler
	VGA (RGB/HV or YPbPr)	(1) 15-pin D-Sub Connector, up to 1080p
	S-Video	(1) 4-pin Mini-DIN Connector
	NTSC Composite Video	(1) RCA Jack
Audio Input	(2) Channels R-L	(2) RCA Jacks (unbalanced stereo)
Audio Output	(2) Channels R-L	(2) RCA Jacks (unbalanced stereo)
Network	10/100Mbps	(1) RJ-45
	Wireless LAN (iSignager-500AWL)	802.11b/g Internal MiniPCI with (2) external antennas
Network Protocol	Supports DHCP and Static IP	
USB	USB 2.0 High-Speed	(2) USB A-type Connectors
Power	12VDC Input, Approx 8W	90VAC-240VAC, 50-60Hz 60W AC-DC Power Adapter
Storage	(1) 44-pin IDE Connector, 2.5" Internal Drive Bay	
	(1) USB 2.0 Port for External Drive	
	(1) Compact Flash Type I or Type II with Lockable Cover	
Operating Temperature/Humidity	0° to 50°C, Humidity 5-90%	
Dimensions (WxHxD)	187.2mm X 46mm X 133.7MM	



Ordering Information

- iSignager-500A-R10 Network Digital Signage Player
iSignager-500AWL-R10 Network Digital Signage Player with 802.11g wireless LAN Module and Antenna

6185 Paseo del Norte • Carlsbad, CA 92011
Telephone: 800-542-0592 • Fax: 858-759-0576

Sales: sales@icpads.com • Technical Support: support@icpads.com • Website: www.icpads.com