



## Introduction

iSignager-LCD 15/17/19 All-in-one Network Digital Signage Display provides a complete hardware and software solution that can be implemented into your application without any cumbersome installation. Within minutes of installation your own advertisements can be displayed on your iSignager-LCD. Your advertisements can be updated anytime, anywhere to ensure that your message reaches your complete target audience. The iSignager-LCD is an ideal solution for retail stores, restaurants, DMV, hospitals, amusement parks, and airports.

## Features

- Intuitive drop & drag editing
- No fixed templates, customization is easy
- Flexible scheduling system ensures that your message reaches your target market
- Real time Video/Audio Inputs
- Built-in WIFI (802.11b/g)
- Built-in Speakers
- 1GB Compact Flash Card included
- OSD Remote Control
- Ambient light sensor

## Main Specifications

	Model	iSignager-LCD-15	iSignager-LCD-17	iSignager-LCD-19
<b>LCD</b>	LCD Size	15"	17"	19"
	Resolution (max)	1024 x768	1280 X 1024	
	Brightness (cd/m <sup>2</sup> )	350	300	
	Contrast Ratio	400:1	800:1	
	LCD Color	262K	16.7M	
	Pixel Pitch (mm)	0.297(H) x 0.297 (V)	0.264 (H) x 0.264 (V)	
	Viewing Angle (H-V)	120/100	160/160	
	Backlight MTBF	50,000 Hours		
	OSD Function	7 Key		
	Auto Dimming	Ambient Light Sensor		
<b>I/O Interface</b>	Secondary Display	1 x DVI-I (DVI+ VGA)		
	Video In/Audio In	(1) RCA composite jack for video, (1) 3.5mm jack for audio		
	USB	(1) USB 2.0		
	Ethernet	(1) 10/100M Base-T		
	Wireless	802.11b/g		
	Serial Port	(1) RS-232		
	Storage	(1) Compact Flash type II, (1) internal 2.5" HDD		
	Audio Out	(2) 1.5W Amplified Speakers, (1) 3.5mm audio jack		
	Remote Control	Panel ON/OFF, Volume, Brightness/Contrast, OSD		
<b>Power</b>	Input Voltage	12VDC		
	Power Adapter	60W AC-DC Power Adapter 90VAC-240VAC, 50-60Hz		
	Consumption	27W	41W	42W
Construction	ABS + PC Plastic (front panel), Alluminum Alloy			
Operating Temperature	0° ~ 50°C			
Color	Silver & Black			
Mounting	VESA 100 Wall Mounting or Stand			
Dimensions (WxHxD)	393.1 x 308.1 x 61mm	428 x 350 x 65mm	470 x 382.5 x 67mm	
Weight	3.2kg	3.8kg	4.4kg	
Front Panel Protection	IP64			

## Ordering Information

iSignager-LCD-15	iSignager-LCD with 15" LCD and 1GB Compact Flash
iSignager-LCD-17	iSignager-LCD with 17" LCD and 1GB Compact Flash
iSignager-LCD-19	iSignager-LCD with 19" LCD and 1GB Compact Flash

6185 Paseo del Norte • Carlsbad, CA 92011  
Telephone: 800-542-0592 / Fax: 858-759-0576

Sales: [sales@icpads.com](mailto:sales@icpads.com) / Technical Support: [support@icpads.com](mailto:support@icpads.com) / Website: <http://www.icpads.com>